



VLIEGENTHART
SINCE 1839

VLIEGENTHART®- Neodecanoate driers

DESCRIPTION

Vliegenthart has extended the range of products based on neodecanoic acid and offer these products as alternatives to the commonly used 2-ethylhexanoate metal carboxylates for use in coatings, inks, unsaturated polyesters and polyurethanes. The new products are dissolved in D60 or low VOC solvents.

PROPERTIES

The newly extended range are either primary oxidative driers which exhibit rapid surface drying, through polymerising driers which promote drying in the body of the film or auxiliary modifier driers which interact with the primary and through driers to promote a balanced drying profile in alkyd based coatings.

For printing inks and VOC free applications Vliegenthart offers cobalt NDA, manganese NDA and zirconium NDA products dissolved in isopropyl laurate.

RECOMMENDED USAGE

For maximum catalytic activity Vliegenthart recommends combining the appropriate products for the application area.

Our R & D teams will be able to provide effective guidance on the correct product combination and dosage rates. The higher strength products give the end-user greater scope for formulation variation as well as being more cost effective.

AVAILABLE GRADES

Calcium 10% NDA
Calcium 5% Neutral NDA
Cobalt 10% NDA
Cobalt 12% NDA
Manganese 10% NDA
Strontium 18% NDA
Strontium 24% NDA
Zirconium 18% NDA
Zirconium 12% NDA
Zinc 12% NDA

Mix driers and others available on request.



VLIEGENTHART B.V.
P.O. Box 6330
4000 HH TIEL - HOLLAND
INFO@VLIEGENTHART.COM
WWW.VLIEGENTHART.COM

ZUIDERHAVENWEG 42
4004 JJ TIEL - HOLLAND
TEL +31 (0)344 63 33 36
FAX +31 (0)344 63 16 16

Green by nature

DRYING VEGETABLE OILS
PAINT REMOVERS
COOKED BINDING MEDIA
CLEAR VARNISHES
PAINT DRIERS AND ADDITIVES



February 2023

Version: 1.0.1

VLIEGENTHART

SINCE 1839

VLIEGENTHART®- Neodecanoate driers

STORAGE STABILITY

Should be stored in well-ventilated conditions and kept away from open flame and peroxides.

60 months in unopened original container at temperatures between -15°C and 40°C.

STANDARD PACKAGING

Steel drum – 200 liter

IBC – 1000 liter

The technical information and specifications contained in this data sheet are based on careful investigations and given to the best of our knowledge. Nevertheless circumstances under which the product is used in practice are subject to many variations. VLIEGENTHART BV cannot be held responsible for possible deviations.

BIJ KONINKLIJKE BESCHIKKING
HOFLEVERANCIER



BY APPOINTMENT TO THE COURT
OF THE NETHERLANDS

VLIEGENTHART B.V.
P.O. Box 6330
4000 HH TIEL - HOLLAND
INFO@VLIEGENTHART.COM
WWW.VLIEGENTHART.COM

ZUIDERHAVENWEG 42
4004 JJ TIEL - HOLLAND
TEL +31 (0)344 63 33 36
FAX +31 (0)344 63 16 16

Green by nature

DRYING VEGETABLE OILS
PAINT REMOVERS
COOKED BINDING MEDIA
CLEAR VARNISHES
PAINT DRIERS AND ADDITIVES